

OUT-SIDER® MERIDIAN™ / MICRO FAMILY OF EXTERIOR LIFTS

PRODUCT FEATURES	ASL-250 OUT-SIDER® MERIDIAN™	ASL-225 OUT-SIDER® MICRO™
Lightest-weight, Robust Design	*Total wt. 89 lbs. /42 kg; Best in Class.	Total wt. 65 lbs. /29 kg; Best in Class.
Lowest Profile	ASL-250 sits only 31.5"/80 cm above Receiver Hitch; Best in Class.	ASL-225 sits only 32"/81.3 cm above Receiver Hitch; Best in Class.
Modular, Tight Design	Yes; Industry Exclusive, Best in Class. Lift and Platform are held firmly to prevent looseness in folded and loaded positions.	Yes; Industry Exclusive "Lift Mast Angle Adjustment" allows installer to best position Lift tight against the rear of the vehicle. Lift and Platform are secure in folded and loaded positions.
Class I Sport Hitch (1.25") Compatibility Class II (1.25") Compatibility Class III (2") Compatibility	No. Yes; choice of Class II or III Hitch Interface Module. Includes Threaded Hitch Insert to eliminate rattle in receiver tube. No Upcharge.	Yes; Includes Threaded Hitch Insert to eliminate rattle in receiver tube. Yes. No.
Angle Adjustment (for Non-Level Receivers)	Standard Class II or III (Selectable, Angle-Adjustment Settings). Industry Exclusive, Best in Class.	Standard. Industry Exclusive, Best in Class.
Maximum Recommended Lifting Capacity	250 lbs./113 kg Tested to 3X rated capacity; Industry Exclusive.	145 lbs. /65 kg; Best in Class. Tested to 3X rated capacity; Industry Exclusive.
Safety Latch (Prevents Unintentional Lowering)	Yes; Industry Exclusive.	Yes; Industry Exclusive.
Lift Operation	Easy, One-Hand Operation; Fully-Automatic, Keyed Operation with Convenient Control Arm. Guarded Rocker Switch on Safety Latch Release Lever.	Easy, One-Hand Operation. Automatic, Keyed Operation with Convenient Control Arm. Guarded Rocker Switch on Safety Latch Release Lever. Gas-Spring Assist for easy Platform "fold/unfold".
Standard, 3rd-Brake Light & Lighted, License-Plate Holder	Yes; Best in Class.	Option available.
Platform Style(s)	Choice of: Adjustable, 3-Piece, Aluminum Platform (for scooters or power chairs). OR One-Piece, Aluminum Platform (for power chairs only). Adjustable Platform, Industry Exclusive. Features 5 mounting positions, for each positioning tray/side ramp, providing an 8" adjustment range (in 1" increments). This ensures that the mobility device is positioned in the optimum position. Standard features: <ul style="list-style-type: none"> • Dual Entry — Drive On/Off. • Perforated platform design for reduced wind resistance when driving in UP position. 	Attractive, Steel Platform – with durable, metallic-black, powder-coat finish – features Positioning Trays for Scooter Stability. Open-design platform for reduced wind resistance when driving in UP position.
Useable Platform Dimension *Max. Scooter Width *Max. Scooter Wheelbase (wb) *Min. Scooter Wheelbase (wb) *Max. Power Chair Width *Max. Power Chair Wheelbase (wb) *Min. Power Chair Wheelbase (wb) *Overall Deck Dimension *Max. Power Chair Width *Max. Power Chair Wheelbase (wb) *Min. Power Chair Wheelbase (wb) *Overall Deck Dimension	Adjustable Platform 25.9" (65.8 cm) 36.6" (93.0 cm) 28.6" (72.6 cm) 25.9" (65.8 cm) 36.6" (93.0 cm) 28.6" (72.6 cm) 27.3" (69.3 cm) width x 35.7" (90.7 cm) shortest length/ 43.7" (111.0 cm) longest length One-Piece Platform (Power Chair Only) 27.0" (68.6 cm) 30.5" (77.5 cm) Not Applicable. 27.2" (69.1 cm) width x 39.8" (101.1 cm) length	24.5" (62.0 cm) 33.5" (85.1 cm) 30.0" (76.2 cm) Not Applicable. Not Applicable. Not Applicable. Not Applicable. Not Applicable. Not Applicable. Not Applicable. Not Applicable.
Easy & Fast Dealer Installation	Quick, several-bolt assembly. Installs in less than one hour; Best in Class.	Quick assembly. Installs in less than one hour; Best in Class.
Height Adjustment	Height-selectable hitch settings. Hitch Interface fits hitch heights of 9" to 18" from ground.	9-1/2" – 12-1/4" adjustable.

*Weight rating does not include hitch interface module (approx. 9 lbs.) or Swing-Away module (46 lbs.)

PRODUCT FEATURES	ASL-250 OUT-SIDER MERIDIAN	ASL-225 OUT-SIDER MICRO
Applicable Scooters/Power Chairs	Choice of most 3- and 4-Wheel Scooters OR Front / Mid/ Rear-Drive Power Wheelchairs. Industry Exclusive, Best in Class.	Choice of 3-Wheel Travel Scooter or other 3-Wheel Scooters weighing up to 145 lbs.; Best in Class.
Scooter Securement	Easy adjustable scooter hold-tite foot. Secures scooters with a deck height of approximately 3-1/2" – 7".	EZ Tie-down strap safely secures scooter to platform.
Power Chair Securement	Optional 3-Point, Color-Keyed, Exterior-Grade, Self-Tensioning Belts with easy-release tabs for persons with limited finger dexterity. Industry Exclusive, Best in Class.	Not Applicable.
Stainless Steel Hardware	Yes; Industry Exclusive.	Yes; Industry Exclusive.
Paint Finish	Acid-treated and powder-coated finish for maximum rust resistance.	Acid-treated and powder-coated finish for maximum rust resistance.
Main Mast Design	Proven Exterior Actuator Mount designed for reliable, long-term use. Actuator is easy to maintain and service. Industry Exclusive, Best in Class.	Whisper-Quiet R ³ ™ Belt / Motor Design. Industry Exclusive, Best in Class.
Robust Electrical System	Key Switch and High-Current Relays for reliability and safety. Best in Class.	Key Switch and High-Current Relays for reliability and safety. Best in Class.
Manual Crank Backup	Yes.	Not Available.
Optional Bruno Pow'rPac Compatible	Yes; Best in Class.	Yes; Best in Class.
Meridian Swing-Away		
Optional, New, Meridian Swing-Away	Yes; Class III. Yes; Class II (March '05).	Yes; Class III. Yes; Class II (March '05).
Weight Compensation Adjustment	Yes; Industry Exclusive.	Yes; Industry Exclusive.
Swing-Away Operation	Yes; Spring-Loaded Lever secures into latched position. Easy One-Hand Operation.	Yes; Spring-Loaded Lever secures into latched position. Easy, One-Hand Operation.
Lightweight Design	Yes; 46 lbs. Adds only 36 lbs. to weight of Lift when hitch-tube assembly is removed. Meridian and Swing-Away weigh only 145 lbs.; Best in Class.	Yes; 46 lbs. Adds only 36 lbs. to weight of Lift when hitch-tube assembly is removed. Micro and Swing-Away weigh only 101 lbs.; Best in Class.
Height Adjustment	Yes; Lift can be mounted to Swing-Away in any of three mounting positions, covering a range of 6".	Yes; Lift can be mounted to Swing-Away in any of three mounting positions, covering a range of 6".
Wiring Harness Mounting Rails	Extra-long, Wiring Harness accommodates Swing-Away without requiring potentially troublesome splices or connectors. Mounting Rails secure the Wiring Harness for reliability and ease of installation.	Extra-long, Wiring Harness accommodates Swing-Away without requiring potentially troublesome splices or connectors. Mounting Rails secure the Wiring Harness for reliability and ease of installation.
Car Wash Compatible ("Touchless" Only)	Yes.	Yes.
Safety: Extensive Dynamic Testing for Safety and Durability	Yes; Industry Exclusive. Road & Laboratory Tested by Certified Testing Facility.	Yes; Industry Exclusive. Road & Laboratory Tested by Certified Testing Facility.
Bruno Customer Satisfaction	1-Year Limited Warranty.	1-Year Limited Warranty.
Car Manufacturer Mobility Rebate Reimbursement	Yes.	Yes.

*Weight rating does not include hitch interface module (approx. 9 lbs.) or Swing-Away module (46 lbs.)



1780 Executive Drive, P.O. Box 84
Oconomowoc, WI 53066
(262) 567-4990 • FAX (262)953-5501
www.bruno.com